

# OPI4BL28IR

## 4MP IP HD IR Outdoor Bullet

### KEY FEATURES

- 4 Megapixel True Day/Night
- IP67 - Internal and external installations
- Integrated IR illumination - low light conditions
- Fixed lens - wide angle
- H.265 smart codec - efficient compression (reduced network traffic)



Features		OPI4BL28IR Feature Specification
<b>Camera</b>	Image Sensor	1/3" 4 Megapixel progressive CMOS
	Effective Pixels	2560(H)x1440(V)
	Electronic Shutter Speed	Auto/Manual, 1/3-1/100000s
	Minimum Illumination	0.5Lux/F2.0 (Colour, 1/25s) 0Lux/F2.0 (Mono IR on)
	IR Distance	Distance up to 30m (98ft)
<b>Lens</b>	Focal Length	2.8mm
	Max. Aperture	F2.0
	Angle of View	H:101°/V:54°
<b>Video</b>	Resolution	4MP (2560x1440)/3MP (2304x1296)/1080P (1920x1080)/720P (1280x720) VGA (640x480)/D1 (704x576/704x480)/CIF (352x288/352x240)
	Frame Rate	Main Stream: 4M (1-20fps) Sub Stream: D1 (1-25/30fps)
	BLC Mode	BLC/HLC/DWDR
<b>Network</b>	Smart Phone	iOS, Android
<b>Certifications</b>	Certifications	CE: (EN 60950:2000)
<b>Electrical</b>	Power Supply	DC12V, PoE (802.3af) (Class 0)
	Power Consumption	<4.2W
<b>Environmental</b>	Operating Conditions	-30°C-60°C (-22°F-140°F)
	Storage Conditions	-30°C-60°C (-22°F-140°F)
	Ingress Protection	IP67
<b>Construction</b>	Casing	Metal
	Dimensions	164.7mm x 70mm 71.6mm (6.48" x 2.76" x 2.82")
	Net Weight	0.38kg (0.84lb)
	Gross Weight	0.49kg (1.08lb)

### ORDERING INFORMATION

0485880 OPI4BL28IR

#### Associated brackets:

0486020 OPJB1 Junction box 1  
0486920 OPSPMA Side pole mount adaptor (Requires OPJB1)